

Specifications — SI 26W In-wall Speaker

Audio/acoustic and electrical

Speaker type.....	2-way in-wall speaker
Frequency range.....	40 Hz to 20 kHz, -10 dB, half space
Power capacity	30 W continuous pink noise 60 W continuous program
Nominal sensitivity.....	89 dB SPL, 1 W, 1 m, half space
Nominal impedance	8 ohms
Crossover frequency	2.5 kHz
Woofer.....	6.5" (165 mm) polypropylene cone with moisture resistant coating
Tweeter	0.75" (19 mm) titanium dome
Input connector	(1) 5 mm captive screw connector, 2 pole

General

Package.....	2 speakers (1 pair)
Temperature/humidity.....	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Mounting.....	Wall mountable with included hardware
Baffle type.....	Plastic, open back, infinite baffle design, front flush with wall
Baffle outer dimensions.....	12.1" H x 8.7" W x 3.1" D (307 mm H x 220 mm W x 80 mm D) from the front of the grill to the back of the woofer 2.9" D (73 mm D) from the front of the wall surface to the back of the woofer
Cutout dimensions.....	10.8" H x 7.4" W (274 mm H x 188 mm W)
Product weight	Single: 3.0 lbs (1.4 kg)
Shipping weight	Pair: 10 lbs (4.5 kg)
Warranty	5 years parts and labor

NOTE All nominal levels are at $\pm 10\%$.

NOTE Specifications are subject to change without notice.

7.6-062508-D7